## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Suppl	ier's	name	or	trade	mark:	Vibia
-------	-------	------	----	-------	-------	-------

Supplier's address: Vibia Lighting, progres 4-6, 08850 Gava gava Barcelona, ES

Model identifier: 740093/15

_	•		
Typa	Λt	liaht	source:
IVDE	VI.	IIKIIL	source.

Type of light so	urce:			
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS
Light source cap	o-type	Renobable PCB		
(or other electric interface)				
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	Yes
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	parameters:	
٠,	mption in on- 100 h), rounded st integer	4	Energy efficiency class	F
dicating if it refo a sphere (360º) (120º) or in a na	s flux (φuse), in- ers to the flux in , in a wide cone arrow cone (90º)	449 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P <sub>on</sub> ), expressed in W		4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,10
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90
Outer dimen-	Height	260	Spectral power dis-	See image
sions without	Width	260	tribution in the range 250 nm to 800 nm, at full-load	in last page
separate con- trol gear, light- ing control	Depth	90		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,458		
		nates (x and y)	0,413		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	46	Survival factor	-		
the lumen maintenance factor	-				

(a)'-': not applicable; (b)'-': not applicable;

