Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: Tob | ias Grau GmbH |
|------------------------------------|---------------|
|------------------------------------|---------------|

Supplier's address: Reparaturservice, Siemensstrasse 35b, 25462 Rellingen Pinneberg, DE

Model identifier: BR 03 1614 Falling in Love

Width

Depth

sions without

separate con-

trol gear, light-

control

ing

| Type of light source: | Type | of light | source: |
|-----------------------|------|----------|---------|
|-----------------------|------|----------|---------|

| Lighting technology | / used: | LED | Non-directional or directional: | NDLS | | |
|---|---|-------------------------|--|-----------|--|--|
| Light source cap-ty | ре | Steckklemme | | | | |
| (or other electric in | iterface) | | | | | |
| Mains or non-main | s: | NMLS | Connected light source (CLS): | No | | |
| Colour-tuneable lig | ht source: | No | Envelope: | - | | |
| High luminance ligh | nt source: | No | | | | |
| Anti-glare shield: | | No | Dimmable: | Yes | | |
| | | Product para | meters | | | |
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| Energy consumpt mode (kWh/1000 up to the nearest in | h), rounded | 4 | Energy efficiency class | F | | |
| Useful luminous fludicating if it refers a sphere (360°), in (120°) or in a narro | to the flux in a wide cone w cone (90º) | 476 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 789 | | |
| On-mode power pressed in W | (P _{on}), ex- | 4,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 | | |
| Networked stand (P _{net}) for CLS, exp and rounded to the imal | ressed in W second dec- | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 70 | | |
| Outer dimen- He | eight | 2 | Spectral power dis- | See image | | |

27

15

range 250 nm to 800

nm, at full-load

in

the

tribution

in last page

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | |
|--|------|------------------------------|-------|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | |
| | | Chromaticity coordi- | 0,451 | | |
| | | nates (x and y) | 0,405 | | |
| Parameters for LED and OLED light sources: | | | | | |
| R9 colour rendering index value | 0 | Survival factor | 1,00 | | |
| the lumen maintenance factor | 0,98 | | | | |

(a)'-': not applicable; (b)'-': not applicable;





