## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	PACPCB

Supplier's address: Produzione Moduli LED, Via del Lavoro, 271, 37050 Angiari Verona, IT

Model identifier: CST0031

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Altra interfac- cia elettrica		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers
Product parameters			

## Product parameters

Product parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
<u> </u>	mption in on- 00 h), rounded st integer	1	Energy efficiency class	D
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone arrow cone (90º)	149 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 695
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	1,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, (	tandby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	85
Outer dimen-	Height	4	Spectral power dis-	See image
sions without	Width	4	tribution in the	in last page
separate control gear, light-	Depth	23	range 250 nm to 800 nm, at full-load	

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,454
		nates (x and y)	0,400
Parameters for LED and OLED light sources:			
R9 colour rendering index value	15	Survival factor	1,00
the lumen maintenance factor	0,98		

(a)'-': not applicable; (b)'-': not applicable;

