## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Arditi S.p.	).A.
--	------

trol gear, light-

control

ing

Supplier's address: Arditi S.p.A., Via Caberardi 3, 24012 Val Brembilla BG, IT

Model identifier: 039612

Type of light source	Type	of light	source:
----------------------	------	----------	---------

Lighting techno	logy used:	LED	Non-directional or directional:	NDLS
Light source cap	o-type	-		
(or other electri	ic interface)			
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	No
		Product para	meters	1
Parameter		Value	Parameter	Value
		General product p	parameters:	
0,	nption in on- 00 h), rounded st integer	7	Energy efficiency class	F
dicating if it refe a sphere (360°)	s flux (фuse), ineers to the flux in, in a wide cone errow cone (90º)	665 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P <sub>on</sub> ), ex- pressed in W		6,3	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, o	tandby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	5	Spectral power dis-	See image
sions without	Width	155	tribution in the	in last page
separate con-	Depth	32	range 250 nm to 800	

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,450			
		nates (x and y)	0,410			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	6	Survival factor	1,00			
the lumen maintenance factor	0,95					

(a)'-': not applicable; (b)'-': not applicable;

