


## A-ROUND 150

<b>Light distribution</b>	Symmetric
<b>Protection class</b>	Class II
<b>Beam angle</b>	50°
<b>Mounting</b>	Ground
<b>Lamps description</b>	Power Led: 8W - 663 lm - 3000K/CRI 80 - 110-240V
<b>Environment</b>	Outdoor
<b>Notes</b>	We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

<b>Technical description</b>	External body made of stainless steel AISI 316L treated with the PVD process (Physical Vapour Deposition). Thanks to this innovative treatment, after the polishing or brushing process, according to the finishing choice, the surfaces of A-Round are coated with a thin film of metals such as zirconium and titanium which, combining with the steel at the molecular level, increase the resistance to both mechanical and to atmospheric agents, permitting the execution of elegant and durable finishings. The body of the luminaire is made of die-cast aluminum EN AB-47100 with low copper content, coated with two layers of paint with high resistance to corrosion. High-strength tempered clear glass, screen-printed to reduce glare. Driver for remote installation included, provided with M12 quick connector for watertight coupling. Installation requires a housing for flush mounting, to be ordered separately. It is necessary to provide an adequate level of gravel (> 300 mm) or a drain system to ensure drainage and avoid water stagnation. To ensure the sealing of the cable gland it is necessary to use flexible electric cables suitable for use in outdoor environments.
------------------------------	---



### A-Round 150

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 110/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

	F4575015	Polished Copper
	F4575046	Brushed Bronze
	F4575044	Brushed Gold
	F4575056	Shoot peened steel

### DIMENSIONS




### ELECTRICAL


<b>Transformer type</b>	Electronic
<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Emergency</b>	Without
<b>Voltage (V)</b>	110/240

### PHYSICAL

<b>Aiming</b>	Adjustable
<b>IK rating</b>	10
<b>Diameter (mm)</b>	150
<b>Number of heads</b>	1

### CERTIFICATIONS










## A-Round 150

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 110/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

-  F4575015 Polished Copper
-  F4575046 Brushed Bronze
-  F4575044 Brushed Gold
-  F4575056 Shoot peened steel

## DIMENSIONS



## CERTIFICATIONS



## A-Round 150 .Accessories

### Optical



 F4555000

Honeycomb. I unit Kit

 F4558000

Flood lens. I unit Kit


## A-Round I50 .Accessories

### Mounting



○ F4597000

### Remote Housing




### A-Round I50

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 110/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

- F4575015 Polished Copper
- F4575046 Brushed Bronze
- F4575044 Brushed Gold
- F4575056 Shoot peened steel

### DIMENSIONS



### Electrical



○ F1206000

**3/4 way terminal block 3 poles IP68**  
7-12 mm cables



○ F990C00A000

**2 way terminal block 3 poles IP68**  
7-12 mm cables

### CERTIFICATIONS



## A-Round 150 . Lamps



### Power LED

### Lamp category:


LED

### Socket:

Special base

### Lamp type:

Power LED




### A-Round 150

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 110/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

- F4575015 Polished Copper
- F4575046 Brushed Bronze
- F4575044 Brushed Gold
- F4575056 Shoot peened steel

### DIMENSIONS



### CERTIFICATIONS

