

#### A-ROUND 315

Light distributionSymmetricIn the symmetry classClass IIBeam angle10°MountingGround

**Lamps description** Power Led: 42W - 3978 lm - 3000K/CRI 80 - 220-240V

**Environment** Outdoor

**Notes**We recommend using a connection system with a degree of protection greater than or equal to the degree of protection

of the luminaire.

**Technical description** External body made of stainless steel AISI 316L treated with the PVD process (Physical Vapour Deposition). Thanks to this

innovative treatment, after the polishing or brushing process, according to the finishing choice, the surfaces of A-Round are coated with a thin film of metals such as zirconium and titanium which, combining with the steel at the molecular level, increase the resistance to both mechanical and to atmospheric agents, permitting the execution of elegant and durable finishings. The body of the luminaire is made of diecast aluminum EN AB-47100 with low copper content, coated

with two layers of paint with high resistance to corrosion. High-strength tempered clear glass, screen-printed

to reduce glare. Driver for remote installation included, provided with M12 quick connector for watertight

coupling. Installation requires a housing for flush mounting, to be ordered separately. It is necessary to provide an adequate level of gravel (> 300 mm) or a drain system to ensure drainage and avoid water stagnation. To ensure the sealing of the cable gland it is necessary to use flexible electric cables

suitable for use in outdoor environments.




#### A-Round 315

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

F4591015 Polished Copper
F4591046 Brushed Bronze
F4591044 Brushed Gold
F4591056 Shoot peened steel

### **DIMENSIONS**



#### **CERTIFICATIONS**











#### **ELECTRICAL**

Transformer type Electronic
Transformer availability Included
Transformer mounting Integral
Emergency Without
Voltage (V) 220/240

#### **PHYSICAL**

Aiming Adjustable

IK rating10Diameter (mm)315Number of heads1





# A-Round 315 . Accessories

# **Optical**





F4557000

F4560000

Honeycomb. 6 units Kit

Flood lens. 6 units Kit




## A-Round 315

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

F4591015 Polished Copper
F4591046 Brushed Bronze
F4591044 Brushed Gold
F4591056 Shoot peened steel

# **DIMENSIONS**



# **CERTIFICATIONS**











## A-Round 315 . Accessories

# Mounting



F4599000

**Remote Housing** 

## **Electrical**





F1206000

3/4 way terminal block 3 poles IP68

7-12 mm cables

F990C00A000

2 way terminal block 3 poles IP68

7-12 mm cables




## A-Round 315

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

F4591015 Polished Copper
F4591046 Brushed Bronze
F4591044 Brushed Gold
F4591056 Shoot peened steel

# **DIMENSIONS**



## **CERTIFICATIONS**











# A-Round 315. Lamps



#### **Power LED**

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




## A-Round 315

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.

F4591015 Polished Copper
F4591046 Brushed Bronze
F4591044 Brushed Gold
F4591056 Shoot peened steel

## **DIMENSIONS**



# **CERTIFICATIONS**



10





