FLOS

A-ROUND 315

Light distribution	Symmetric
symmetry Insulation class	Class II
Beam angle	25°
Mounting	Ground
Lamps description	Power Led: 42W - 3978 lm - 3000K/CRI 80 - 220-240V
Environment	Outdoor
Notes	We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.
Technical description	External body made of stainless steel AISI 316L treated with the PVD process (Physical Vapour Deposition). Thanks to this innovative treatment, after the polishing or brushing process, according to the finishing choice, the surfaces of A-Round are coated with a thin film of metals such as zirconium and titanium which, combining with the steel at the molecular level, increase the resistance to both mechanical and to atmospheric agents, permitting the execution of elegant and durable finishings. The body of the luminaire is made of die- cast aluminum EN AB-47100 with low copper content, coated with two layers of paint with high resistance to corrosion. High-strength tempered clear glass, screen-printed to reduce glare. Driver for remote installation included, provided with M12 quick connector for watertight coupling. Installation requires a housing for flush mounting, to be ordered separately. It is necessary to provide an adequate level of gravel (> 300 mm) or a drain system to ensure drainage and avoid water stagnation. To ensure the sealing of the cable gland it is necessary to use flexible electric cables suitable for use in outdoor environments

suitable for use in outdoor environments.



A-Round 315

designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.



Polished Copper Brushed Bronze Brushed Gold Shoot peened steel

DIMENSIONS

ELECTRICAL

Transformer type
Transformer availability
Transformer mounting
Emergency
Voltage (V)


Electronic Included Integral Without 220/240

PHYSICAL

Aiming	
IK rating	
Diameter (mm)	
Number of heads	

Adjustable 10 315

I









FLOS





A-Round 315 .Accessories

Optical







F4560000

Honeycomb. 6 units Kit

Flood lens. 6 units Kit

A-Round 315


designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.



Polished Copper Brushed Bronze Brushed Gold Shoot peened steel

DIMENSIONS








F

A-Round 315 .Accessories

Mounting





A-Round 315 . Lamps



Power LED

Lamp category: LED Socket: Special base Lamp type:

Power LED



A-Round 315


designed by Piero Lissoni

Ground-recessed luminaire for outdoor use, walkable and trafficable, available in three sizes, with adjustable optics in various configurations. Integrated 220/240V power source. Remote housing required, to be ordered separately. Dimmable version on request.



Polished Copper Brushed Bronze Brushed Gold Shoot peened steel

DIMENSIONS





CERTIFICATIONS



