




RIME PENDANT LAMP - EU VERSION


TAF STUDIO ON THE DESIGN "Designing simple things is often one of the hardest things to do. We wanted to create a simple lamp with a glass shape, giving it a soft expression while making its top and pendant tube as subtle as possible. We were inspired by the shape of acorns for the gentle lines of the pendant while hinting towards the shaded expression of ice and rime for the glass of the design, allowing for the light to shine slightly through with a refined touch. The Rime Pendant Lamp brings a timeless yet modern perspective to the archetypal light through its translucent shade and graphic form."







READY-TO-SHIP OPTIONS



DESIGNED BY / YEAR OF DESIGN

TAF Studio / 2020

ABOUT THE DESIGNER

TAF Studio is a Stockholm-based design and architecture studio, founded by Gabriella Gustafson and Mattias Ståhlbom. The duo works within product and interior design.

CATEGORY

Pendant lamp

ENVIRONMENT

Indoor

COUNTRY OF PRODUCTION

Poland

DESCRIPTION

Bringing a new perspective to the glass pendant lamp through its mouthblown, translucent glass that has been sandblasted for a refined surface expression. Designed with a characteristic form, complemented by a powder-coated top-part, pendant tube and cord in a matching color for a subtle touch.

MATERIAL

Mouthblown glass shade. Aluminum, powder coated top-piece and pendant tube. PVC cord.

CORD LENGTH

400 cm / 13'1"

BULB INCLUDED

Ø12: Yes Ø25, Ø37, Ø45: No

CEILING CAP INCLUDED

Yes - white ØI2 & Ø25: Ø 9 cm / 3.5" H 5,6 cm / 2.2" Ø37 & Ø45: Ø II cm / 4.3" H 3,5 cm / I.4"

DIMMABLE FUNCTION

Yes, if dimmable bulb is used.

CLEANING AND CARE

Clean with a moist cloth. If necessary use a little dish soap on the cloth.




RIME PENDANT LAMP - EU VERSION














LAMP RATING Ø12

Voltage 220 - 240V Frequency 50/60Hz IP Rating IP2O Classification Class II Socket 1 x G9 Max. 25W

LAMP RATING Ø25

220 - 240V Voltage 50/60Hz Frequency IP Rating IP2O Classification Class II Socket 1 x FI4 Max. 40W

LAMP RATING Ø37

220 - 240V Voltage Frequency 50/60Hz IP Rating IP2O Classification Class I Socket 1 x E27 Max. 60W

LAMP RATING Ø45

Voltage 220 - 240V Frequency 50/60Hz IP9O **IP** Rating Classification Class I 1 x E27 Socket Max. 60W

BULB SPECIFICATION Ø12

ltem G9 LED Watt 3 W Lumen 190 lm/W 2700K Kelvin Lumen Maintenance 20.000h CRI 90 Dimmable Yes

BULB RECOMMENDATION Ø25

Lamp base F14 Ø45 X 80 mm **Dimensions**

Light source shape P45

Recommended

Risk Group

400-800 lm (6-IO W LED) light output LED with opal or frosted Light source type

Except

diffuser

BULB RECOMMENDATION Ø37

Lamp base

Dimensions Ø60 X IIO mm

Light source shape A6O

Recommended

750-I500 lm (8-I2 W LED) light output LED with opal or frosted Light source type

diffuser

BULB RECOMMENDATION Ø45

Lamp base

Dimensions Ø77 X I45 mm

Light source shape A67

Recommended

750-I500 lm (8-I2 W LED) light output

Light source type LED with opal or frosted

diffuser

GENERAL STANDARDS & CERTIFICATES

EU/UK

REACH

Directive - EC/I9O7/2OO6

ROHS Directive - 2011/65/EU amended RoHS 3 Directive 2015/863

ECO Design Directive - 245/2009/EC

WEEE Directive - 2012/19/EU

MUUTO