Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Tobias Grau Gmb	Supplier	s name or	: trade mark:	Lobias	Grau Gmb	эн
--	----------	-----------	---------------	--------	----------	----

Supplier's address: Reparaturservice, Siemensstrasse 35b, 25462 Rellingen Pinneberg, DE

Model identifier: BR 03 1576 JOHN

_	•			
Typa	Λt	liaht	sourc	Δ.
IVDE	OI.	IIGIIL	3 Uui C	c.

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	Steckklemme			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Yes	
Product parameters				
Parameter	Value	Parameter	Value	
General product parameters:				

Parameter		Value	Parameter	Value
General product parameters:				
.	nption in on- 00 h), rounded st integer	10	Energy efficiency class	Е
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 253 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 500
On-mode power (P _{on}), expressed in W		9,5	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without	Height	3	Spectral power dis-	See image
	Width	107	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	72	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,405	
		nates (x and y)	0,389	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	0	Survival factor	1,00	
the lumen maintenance factor	0,98			

(a)'-': not applicable; (b)'-': not applicable;

Light Measurement Report

SPD BR 03 1576



